FISH & RICHARDSON P.C.

One Riverway Suite 1200 Houston, Texas 77056

Telephone 713 629-5070

Facsimile 713 629-7811

September 8, 1997

Attorney Docket No.: 09389/002001

BOX PATENT APPLICATION

Assistant Commissioner for Patents Washington, DC 20231

Presented for filing is a new original patent application of:

BOSTON HOUSTON

Frederick P. Fish

W.K. Richardson

Ø

שׁ

1855-1930

1859-1951

Applicant:

FERNANDO FRIMM, HARRIS I. KNECHT, THOMAS

CONDON

Title

SEMISUBMERSIBLE OFFSHORE VESSEL

Enclosed are the following papers, including all those required for a filing date under 37 CFR §1.53(b):

Pages of Specification 6 Pages of Claims 5 Pages of Abstract

Signed Declaration [To Be Filed At A Later Date]

Sheets of Drawing

Basic filing fee	770.00
Total claims in excess of 20 times \$22.00	0.00
Independent claims in excess of 3 times \$80.00	160.00
Multiple dependent claims	0.00
Total filing fee:	\$ 930.00

"EXPRESS MAIL" Mailing Label Number ET 267842649 U.S

Date of Deposit

I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office To Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

NEW YORK
COUTHERN CALIFORNIA
SILICON VALLEY
TWIN CITIES
WASHINGTON, DC

FISH & RICHARDSON P.C.

September 8, 1997 Page 2

Please charge the filing fee and any other required fees, or apply any credits, to Deposit Account No. 06-1050, referencing the Attorney Docket number shown above. A duplicate copy of this transmittal letter is attached.

If this application is found to be INCOMPLETE, or if it appears that a telephone conference would helpfully advance prosecution, please telephone the undersigned at 713/629-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Respectively submitted,

Alan D. Rosenthal Reg. No. 27,833

Enclosures

APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: SEMISUBMERSIBLE OFFSHORE VESSEL

APPLICANT: FERNANDO C. FRIMM

HARRIS I. KNECHT THOMAS D. CONDON

"EXPRESS MAIL" Mailing Label Number ET 267842649 US

Date of Deposit 9/8/97

I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office To Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Glan D. Rosenthal Aland. Country

10

15

20

25

30

SEMISUMERSIBLE OFFSHORE VESSEL

Background of the Invention

Various types of vessels are commonly used for drilling wells offshore, including barges, jackups, drill ships, and semisubmersibles.

Semisubmersible vessels typically have a superstructure deck or decks supported by columns which are attached to hulls or pontoons which have adjustable ballast capability. By adjusting the ballast carried by the pontoons, the pontoons may be positioned at or near the surface of the water or in a submerged location below the surface of the water, while the superstructure deck remains above the surface of the water. While being moved to a location where the vessel is to be used, the pontoons typically are ballasted to permit them to ride at or near the surface of the water, facilitating transport of the vessel. After reaching the desired location, the ballast of the pontoons may be adjusted to cause the pontoons to become submerged below the surface of the water, providing improved stability and reduced motion of the vessel in rough, deep seas. The vessel may or may not be self-propelled.

The pontoons in turn support the superstructure deck by columns which rise vertically or substantially vertically from the ring pontoon at various locations, as well as braces which may interconnect the pontoons, the pontoons and the columns, the columns and the superstructure, and/or two or more of the columns. The purpose is to provide a strong and substantially rigid base structure to support the deck(s) of the superstructure.

The interior of both the columns and the pontoons may be subdivided by bulkheads to strengthen the structure,

10

15

20

25

to provide enclosed spaces for locating and storing various equipment (e.g., anchors, chains, propulsion mechanisms, etc.), and to provide a plurality of separate tanks for purposes of ballasting the vessel and storing various fluids and other materials which may be required or desired during drilling or produced by the well.

The columns typically have been placed such that the vertical centerline of the columns intersects the axial centerline of the starboard or port pontoon on which the column is located. In a ring pontoon semisubmersible vessel previously proposed, the four corner columns have been placed such that the vertical centerline of the columns intersects the axial centerline of the forward or aft pontoon as well.

Summary of the Invention

The present invention relates to improvements in ring pontoon semisubmersible vessels.

In one embodiment of the present invention, the columns are located such that the centerline of the column is displaced from the axial centerline of the forward and aft sections of the ring pontoon. A vertical partition in each column lies in the same plane as, and therefore forms an extension of, the interior side of either the forward or the aft section of the pontoon ring.

In another embodiment of the invention, the columns also are located such that the centerline of the column is displaced from the axial centerline of the starboard and port sections of the ring pontoon.

10

15

20

25

30

Brief Description of the Drawings

Figures 1, 2, and 3 are the side elevation, cross section, and plan views respectively of one embodiment of the invention.

Figures 4A, 4B, 4C, and 4D show exemplary centerline vertical cross sections of the ring pontoon in various embodiments and at various locations along the ring pontoon.

Figures 5, 6, and 7 are the side elevation, cross section, and plan views respectively of another embodiment of the invention.

Figures 8, 9, and 10 are the side elevation, cross section, and plan views respectively of yet another embodiment of the invention.

Description of the Preferred Embodiments

This invention relates to improvements to ring pontoon semisubmersible vessels.

In a ring pontoon vessel such as is shown in Figures 1, 2, and 3, the forward, aft, starboard, and port pontoons 11, 12, 13, and 14, respectively, form a ring 10. The shape of the ring is not required to be circular, and typically is either substantially square or rectangular, although other shapes (e.g., hexagonal, octagonal, etc.) are possible. The ring 10 shown in Figure 3 may be considered to be substantially rectangular, or may be considered to be octagonal.

The vertical cross section of the ring is either substantially square or rectangular. Other cross sectional shapes (e.g., octagonal, etc.) are possible. The vertical cross-section of the starboard pontoon 13 and the port pontoon 14 is substantially rectangular, having curved edges. While the vertical cross section of the ring may be symmetrical, that is not required.

10

15

20

25

30

Moreover, the vertical cross section of the ring 10 may vary from location to location along the longitudinal axis of the ring. For example, as shown in Figure 4, the vertical cross section of the forward pontoon 11 and/or the aft pontoon 12 may be substantially different from the vertical cross section of either the starboard or port pontoons 13 and 14. Figure 4A is representative of a centerline vertical cross section for the starboard and port pontoons 13 and 14, and also may represent the centerline vertical cross section for the forward and aft pontoons 11 and 12. Alternatively, either or both of the forward and aft pontoons may have a significantly different vertical cross section. Examples of alternative centerline vertical cross sections are shown in Figures 4B, 4C, and 4D, which represent a "barge bow" cross section (Figure 4B), a raised reduced cross section (Figure 4C), and a lowered reduced cross section (Figure 4D). When a reduced cross section is selected for the design of the forward and/or aft pontoon, there will be a transition region 20 at which the cross section of the forward and/or aft pontoon transitions from one cross sectional shape to another.

Typically, the centerline vertical cross sections of the starboard and port pontoons, and the centerline vertical cross sections of the forward and aft pontoons, would be the same, although this is not required. Similarly, the centerline vertical cross sections of all of the pontoons may be the same.

As shown in Figure 3, each pontoon is subdivided by at least one vertical bulkhead 31 which is parallel to the longitudinal axis of the pontoon, and may be subdivided further by one or more vertical partitions or bulkheads 32 which are transverse such axis, into various fluid tight compartments or tanks. Similarly, each column is divided by

10

15

20

25

30

one or more vertical partitions or bulkheads 33 and 34 into multiple compartments or tanks. These partitions or bulkheads also contribute to the structural strength and rigidity of the pontoons and the columns.

Also shown in Figure 3 are four additional tanks or compartments 40 which have been formed, one at each of the interior corners of the ring 10. These additional tanks or compartments further reinforce and become part of the ring 10.

As shown in Figure 3, the vessel uses at least four corner columns 61, 62, 63, and 64, which are connected to the pontoon ring 10 near the forward and aft ends of the starboard and port pontoons, respectively. Additional columns, such as columns 65 and 66, also may be used if desired. The columns support the superstructure deck 70, as shown in Figures 1 and 2, above the pontoon ring 10.

Additional braces 50 may extend radially inward from the ring pontoon 10 to locations on the superstructure deck 70 located inwardly of the ring pontoon 10, and serve to further reinforce and strengthen the vessel.

In one embodiment of the invention, each the corner columns 61, 62, 63, and 64 are located at positions on the ring which permit at least one of the interior vertical bulkheads of such column to be in the same plane as either the interior or exterior surface of the pontoon. As shown in Figure 3, vertical bulkhead 33 in each of the four corner columns lies in the same plane as the interior surface 38 of the forward pontoon or interior surface 39 of the aft pontoon. This permits the vertical bulkhead 33 to be formed as an extension of the interior surface 38 of the forward pontoon or interior surface 39 of the aft pontoon.

Locating each of the four corner columns as described permits the center of each of such column to be

10

15

20

25

30

displaced horizontally from the axial centerline of the forward and aft pontoons, while taking advantage of the structural integrity which results from having a vertical surface of the pontoon be contiguous with and extend into one of the interior vertical bulkheads in the column. By displacing the center of the corner columns horizontally from the axial centerline of the forward and aft pontoons, movement of the superstructure deck due to wave motion is reduced.

In another embodiment of the invention shown in Figures 5, 6, and 7, the positions of the columns are displaced even more, such that an exterior vertical surface of the column lies in the same plane as the opposite surface of either the forward or aft pontoon. Thus, the most forward surface of the column 61 is in the same plane as the most aft vertical surface of the forward pontoon 11, and the most aft surface of the column 62 is in the same plane as the most forward vertical surface of the aft pontoon 12.

In the embodiment shown in Figures 5 6, and 7, braces 50 extend from each of the corner tanks or compartments 40 to the deck of the superstructure 70.

In yet another embodiment of the invention shown in Figures 8, 9, and 10, the positions of the four corner columns have been displaced not only from the axial centerlines of the forward and aft pontoons, but also from the axial centerlines of the starboard and port pontoons. This permits even further reduction of the movement of the superstructure deck due to wave action, while retaining a very strong and rigid base structure.

What is claimed is:

6 of the pontoon ring.

1	1. A semisubmersible vessel comprising:
2	(a) a superstructure deck;
3	(b) a ring pontoon having forward, aft,
4	starboard, and port sections;
5	(c) said forward and aft pontoon
6	sections each having a centerline partition;
7	(d) said superstructure deck supported
8	by at least four columns located near the
9	forward and aft ends of the starboard and
LO	port sections of the ring pontoon;
L1	(e) a first interior vertical partition
L2	in each of such four columns lying in the
L3	same plane as a side of either the forward or
L4	aft section of the pontoon ring.
1	2. A semisubmersible vessel according to claim 1
2	further comprising a second interior vertical partition
3	which is transverse to said first interior vertical
4	partition and which lies in the same plane as a vertical
5	interior partition in either the starboard or port section

1.	3. A semisubmersible vessel comprising:
2	(a) a superstructure deck;
3	(b) a ring pontoon having forward, aft,
4	starboard, and port sections;
5	(c) said superstructure deck is
6	supported by at least four columns located
7	near the forward and aft ends of the
8	starboard and port sections of the ring
9	pontoon; and
10	(d) the vertical centerline of each of
11	the columns is located inward of both the
12	axial centerline of the forward section of
13	the ring pontoon and the axial centerline of

1 4. A semisubmersible vessel according to claim 3 2 in which the outer perimeter of the ring pontoon forms an 3 octagon.

the aft section of the ring pontoon.

- 5. A semisubmersible vessel according to claim 3 in which the inner perimeter of the ring pontoon forms an octagon.
- 1 6. A semisubmersible vessel according to claim 3 2 in which the superstructure deck is further supported by at 3 least four radial braces running from the ring pontoon to 4 locations on the superstructure deck which are inboard of 5 the ring pontoon.

1	7. A semisubmersible vessel comprising:
2	(a) a superstructure deck;
3	(b) a ring pontoon having forward, aft,
4	starboard, and port sections; and
5	(c) said forward and aft sections of
6	the ring pontoon having a reduced sectional
7	height compared with the starboard and port
8	sections of the ring pontoon.

8. A semisubmersible vessel according to claim 7 in which the outer perimeter of the ring pontoon forms an octagon.


1	9. A semisubmersible vessel comprising:
2	(a) a superstructure deck;
3	(b) a ring pontoon having forward, aft
4	starboard, and port sections;
5	(c) said superstructure deck is
6	supported by at least four columns located
7	near the forward and aft ends of the
8	starboard and port sections of the ring
9	pontoon; and
10	(d) the vertical centerline of each of
11	the columns is located inward of the axial
12	centerlines of the forward, aft, starboard,
13	and port sections of the ring pontoon.


1	10. A semisubmersible vessel comprising:
2	(a) a superstructure deck;
3	(b) a non-square ring pontoon;
4	(c) said superstructure deck is
5	supported by more than four columns located
6	in spaced relation along the ring pontoon.


SEMISUMERSIBLE OFFSHORE VESSEL


Abstract of the Disclosure

Improvements to a ring pontoon semisubmersible vessel. The centerlines of the corner columns ar displaced with respect to the axial centerlines of the forward and aft portions of the ring pontoon. Additionally, the centerlines of the corner columns may be displaced with respect to the axial centerlines of the starboard and port portions of the ring pontoon. The superstructure deck may be supported by radial braces extending from the ring pontoon to locations on the superstructure deck which are inward of the ring pontoon.













** .1









COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled SEMISUBMERSIBLE OFFSHORE VESSEL, the specification of which is attached hereto. was filed on _____ as Application Serial No. _____ and was amended on _____ . and was amended on ______.

was described and claimed in PCT International Application No. ______ filed on ______ and as amended under PCT Article 19 on ______. I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56. I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Margaret A. Boulware, Reg. No. 28,708; John D. Cowart, Reg. No. 38,415; Albert B. Deaver, Reg. No. 34,318; Alan H. Gordon, Reg. No. 26,168; Daniel C. Hu, Reg. No. 40,025; Todd D. Mattingly, Reg. No. 40,298; Jonathan P. Osha, Reg. No. 33,986; Fred G. Pruner, Jr., Reg. No. 40,779; Alan D. Rosenthal, Reg. No. 27,833; Howard L. Speight, Reg. No. 37,733; Michael O. Sutton, Reg. No. 26,675; Jon R. Trembath, Reg. No. 38,344; Mason A. Gross, Reg. No. 40,006; William R. Johnson, Reg. No. 32,875; and John C. Phillips, Reg. No. 35,322 Address all telephone calls to Alan D. Rosenthal at telephone number 713/629-5070. Address all correspondence to Alan D. Rosenthal, Fish & Richardson P.C., One Riverway, Suite 1200 , Houston, TX 77056. I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon. Full Name of Inventor: Fernando C. Frimm Inventor's Signature: _____ Date: _____ Residence Address: Houston, Texas Citizen of: Brazil Post Office Address:

COMBINED DECLARATION AND POWER OF ATTORNEY CONTINUED

Full Name of Inventor: <u>Harris I. Knecht</u>		
Inventor's Signature:	Date:	
Residence Address: <u>Houston, Texas</u>		
Citizen of: USA		
Post Office Address:		
Full Name of Inventor: Thomas D. Condon		
Inventor's Signature:	Date:	
Residence Address: Houston, Texas		
Citizen of: USA		
Post Office Address:		